



Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au

25th July 2019

SPECIFICATION SHEET

Code: ADVHWRAP20N

Description: WRAP HAND 500MM 450MT 20UM CLEAR
Core ID: 58 mm

PROPERTY		UNITS	VALUES	TEST METHOD
Thickness		Micron	20	Thickness Measurement
Stretch Level		%	>290	Highlight Tester
Tensile Strength	MD	Mpa	45	ASTM D 882 (JIS Z-1702)
	TD		27	
Elongation	MD	%	595	ASTM D 882 (JIS Z-1702)
	TD		738	
Tear Strength (Elmendorf)	MD	gm	89	ASTM D 1922 (JIS P-8116)
	TD		323	
Impact Strength (Drop Dart)		gm	125	ASTM D 1709
Cling		Gm	225	IPG METHOD
Pre-stretch (% at break)		%	298	HIGHLIGHT

Julie Butcher

Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.

