



Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au

25th July 2019

SPECIFICATION SHEET

Code: ADVMCWRAP25B

Description: WRAP MACHINE 500MM 1250MT 25UM BLACK

Core ID: 58 mm

PROPERTY	UNITS	VALUES	TEST METHOD
Thickness	Micron	25	Thickness Measurement
Stretch Level	%	>310	Highlight Tester
Tensile Strength MD	Mpa	50	ASTM D 882
TD		31	(JIS Z-1702)
Elongation MD	%	620	ASTM D 882
TD		775	(JIS Z-1702)
Tear Strength MD	gm	101	ASTM D 1922
(Elmendorf) TD		333	(JIS P-8116)
Impact Strength (Drop Dart)	gm	135	ASTM D 1709
Cling	Gm	225	IPG METHOD
Pre-stretch (% at break)	%	328	HIGHLIGHT

Julie Butcher

Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.

