



Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

Issue Date: 15th August 2019

Code: ALL300WNS/4-14 Description: GUMBOOT PU A/CARE WHT N/SFTY LW 4-14

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au





Polyurethane Boots
P6000 (Soft Toe)
P6001 (STC)

FEATURES
Size range: 4 - 14
Upper: PU Upper
Sole: PU Sole
Colours: White Upper / Blue Sole
Accreditations:
EN ISO 20345:2011 BA A SRC
EN ISO 20347:2012 OB A SRC
EU (CE)

PU

FLEX TESTED TO OVER 900 000 FLEXES
WITH NO SIGNIFICANT DETERIORATION.

Equates to over 900 000 steps or 120 hours of non-stop walking.
Flex test standard is to 150 000 flexes.

MORE COMFORT, LESS FATIGUE

Upper	<ul style="list-style-type: none"> PU upper is light in weight for enhanced comfort to the wearer and anti-fatigue support PU offers enhanced thermal properties to provide good insulation against heat and cold PU offers 2-3 times more durability than PVC material increasing the lifespan of the boot PU offers excellent water resistance and enhanced defense against fats, acids, oils and chemicals Reinforced ankle guard Kick-off spur for easy removal of boot Minimal cosmetic features for reduced bacterial contamination Standard with a PU cushioned insole for enhanced comfort and reduced fatigue
Insole	<ul style="list-style-type: none"> Anti-static, anti-bacterial and anti-fungal PU insole comprising 80% elastopan for comfort and hygiene. Footbed is treated with Ultrafresh, a powerful anti-bacterial and anti-fungal agent, and perforated with anti-static stitching.
Sole	<ul style="list-style-type: none"> PU sole offers 2-3 times more durability than PVC material increasing the lifespan of the boots in the presence of acids, oils and chemicals The cleated sole provides SRC slip-resistance rating and is recommended for slippery conditions and offers easy-cleaning properties
Toe Cap	<ul style="list-style-type: none"> Steel toe cap with impact resistance of 200 joules (EN 12568)
Lining	<ul style="list-style-type: none"> Printed polyester PU lining with anti-microbial and anti-bacterial properties
Last	<ul style="list-style-type: none"> Designed with optimal toe spring for walking and kneeling

Julie Butcher Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.

