

30th May 2015

Bunzl Food Processor Supplies Pty Ltd ABN 17 000 011 441

Sydney 34-48 Cos

34-48 Cosgrove Road Enfield NSW 2136 Locked Bag 3011 Burwood NSW 2134

Australia

Tel: +61 2 9737 2100 Fax: +61 2 9642 0229 www.bunzl.com.au

PRODUCT SPECIFICATION

PRODUCT: APE1000397 - FILM 50CM X 17MIC X 800 MTRS RMF

DESCRIPTION: IPG Rapfast Meat film is a plasticized PVC food grade stretch/cling film

exhibiting high clarity, excellent cling and excellent preservative

characteristics for most fresh and frozen foodstuffs.

It has been specifically developed for use with auto-wrapping machines

and hand wrapping applications.

COLOUR: Natural

THICKNESS: Nominal +/-3µm

WIDTH: Nominal +2mm - 0mm

LENGTH: Nominal +10mm - 0m

TENSILE STRENGTH: Transverse 18 - 28mpa

(Instron) Machine 17 – 26mpa

ELONGATION: Transverse 190% - 360%

(Instron) Machine 150% - 300%

HEAT SEALING: 135° - 160°C

(0.5sc/2kg/cm²)

WVTR: 13 - 25gms/m²/hr

(ATSM E96-53 method L)

GAS TRANSMISSION: 0²: 2300 - 3000cc / 100in² / 24hrs (LINDE) CO²: 1600 - 1850cc / 100in² / 24hrs

COMPOSITION: IPG Rapfast Meat film is manufactured from a proprietary formula

comprising a PVC resin / Plasticizer / Antifog-Antistatic / Stabilizer /

Lubricant blend tailored to the specified applications.

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate.

COMPLIANCE:

The films comply with Australian Standard AS2070 "Plastic Materials for Food Contact Use" and with relevant regulations of the United States of America Food and Drugs Administration as set out in the Code of Federal Regulations 21CFR Parts 170 to 199 and any subsequent amendments or revisions.

SAFETY:

PVC Film is essentially self extinguishing due to its chlorine content. However if it is lit, it may evolve hydrogen chloride gas (a corrosive material) so great care must be exercised.

Ensure that children do not place film over nose and/ or mouth

STORAGE:

The film should not be subjected to prolonged extremes of temperature or direct sunlight and should ideally be stored below 20°C. This product is manufactured in roll form and should be stored in an upright position.

Suke Butcher.





