ADAPT™ RANGE

POWER

The Power is designed for the workers that need the toughness of a boot but require the ankle mobility of a shoe. Ideal for drivers and people walking big distances on tough terrain. Built on the ***ADAPT***™ sole technology and ***articulated*FIT** upper the Power is designed to improve adaption to rough surfaces and is combined with a lightweight design to assist in minimising fatigue and maximising performance.



SIZES 4-13
1/2 SIZES 6.5-10.5
WEIGHT 605g

COLOURS

PERFORMANCE SYSTEMS

SYST-**M**®	Design philosophy that integrates series of technologies and design features to provide movement specific support and flexibility.
ADAPT™	Sole unit technology designed to maximise adaption to uneven terrain and reduce injury risks.
*articulated***FIT**™	Upper design system to allow the natural movement of the foot and ankle from heel strike to toe-off.
asym***BEVEL***™	Heel shaped to match the natural heel strike position during walking to maximise contact area and provide a smooth ride.
Ortholite®	Breathable memory foam insole that moulds to the foot providing a customised fit and helping to reduce in-shoe friction.
*decouple***GROOVE**™	Flex groove along the length of the sole to provide flexibility to allow a smooth transition from initial contact to foot flat and improve terrain adaption.
softboard™	Constructed on cushioned foam insole board for a smooth ride.
radiator**TECH**™	Manufacturing technique used to improve the breathability of leather and lining materials.
endurelon™	Specifically compounded phylon midsole to improve cushioning rebound characteristics and durability.
WIDEcap	Wide anatomical shaped toecap to reduce rubbing and nerve impingement.
FIT*CHECK*	Registered fitting guide printed on the insole to indicate thecorrect spacing between the end of the longest toe and the toecap.

SAFETY SYSTEMS

COMPOSITE Toecap	Lightweight, metal-free, nonconductive, insulating and airport friendly safety toecap that complies with (AS/NZS 2210.3), (EN-ISO 20345) and (ASTM F2413-11) standards.
*slip***RESIST**-C	Sole slip resistant to soap (SLS) on ceramic tiles and glyceryl on steel plate.
300˚c*HeatResistant*	Nitrile rubber sole that is hard wearing and resistant to extreme heat.
*fueloil***RESIST**	Sole resists breakdown to fuel oil.
ANTI-STATIC	Minimises static electricity build up for safety in volatile environments.
H_2O*RESISTANT*	Footwear designed to shed water.
Scuff**CAP**	Improves durability in high wear zones.
LOWcatch*sole*	Low profile sole at the toe to reduce the risk of tripping.
REFLECTIVE	Upper contains retro-reflective material to improve visibility in low light conditions.

HAZARD SOLUTION GUIDE

SLIPS

- Uneven surfaces: ***ADAPT***™ sole unit is designed to maximise adaption to uneven terrain to maintain traction and reduce injury risks.

TRIPS & FALLS

- Lightweight footwear to reduce fatigue of the leg muscles that lift the toes.
- **LOW**catch*sole* to improve swing phase ground clearance at the toe to reduce the risk of tripping.
- asym***BEVEL***™ to match the natural heel strike position during walking to minimise fatigue of the leg muscles that lift the toes.
- ***ADAPT***™ range to assist in foot adaption to uneven terrain.

SPRAINS

- *articulated***FIT**™ upper to provide targeted support and flexibility to improve adaption to uneven terrain.
- ***ADAPT***™ range to assist in foot adaption to uneven terrain.

COMBUSTIBLE MATERIALS

- **ANTI**-STATIC certified footwear minimises static electricity build-up for safety in volatile environments.
- Metal-free footwear can reduce the risk of spark ignition.

HOT CONTACT

- **300°c***HeatResistant* nitrile rubber outsole provides protection in high heat environments. Ideal for workers in road construction and other occupations that expose workers to hot surfaces or objects.

PRODUCT DETAILS

APPROVED STANDARDS

- AS/NZS 2210.3 (Class I S1 SRC HRO)
- EN – ISO 20345 (S1 SRC HRO)
- ASTM F2413 – 11 (M/I/75/C/75/SD)

OUTSOLE: Nitrile Rubber

TOECAP: Composite

UPPER: Full Grain Leather

PRODUCT CODES:
xxx represents sizing i.e. size 12 is 120 and size 9.5 is 095

BLACK BOOT CODE:
MKPOWER-BBFxxx

FIT GRID



SOLE SELECTION GRID



MACKBOOTS.COM.AU | 1300 350 216

Mack Footwear is sold under licence from Mack Trucks, Inc. All rights reserved. *Weight disclaimer. Footwear weights are based on a men's UK8 for a single shoe or boot and a ladies UK10 for women's shoes. Due to the nature of manufacturing there will be subtle variation between pairs. Disclaimer: Every reasonable effort has been made to ensure the accuracy of the Product information in this document. This document must not be regarded as an infallible guide. **Mack Boots**™ accepts no responsibility in this regard. As product details may change from time to time please contact **Mack Boots**™ to gain the latest information.

benchmark PRODUCT CERTIFICATION

AS/NZS 2210 Australian /New Zealand Standards
EN - ISO 20345 European Standards
ASTM F2413 American Standards