

FIBROUS CASINGS



PRODUCT DESCRIPTION

Viscofan Fibrous is a fibrous casing obtained from regenerated cellulose and it includes an abaca paper sheet that provides additional strength. It can be supplied in a variety of presentations.

Fibrous casings can be provided as Efinet F, a special type of converting with netting on top. Please, consult availability and conditions.

Fibrous casings can be provided as T-Shirr and cut pieces with loop and/or clip.

PRODUCT APPLICATION

Fibrous casings are typically used for the production of cooked meat products, smoked or not, but they are also used to produce dry-fermented products and other non-meat products like cheese. Additionally, fibrous casings can be used in other non-food applications.

Viscofan keeps the right to modify this sheet totally or partially. The information included herein has been collected by Viscofan S.A. in good faith and to the best of its knowledge. It must be considered as a communication of the experience accumulated over the years by Viscofan S.A. without any implicit or explicit guarantee from the side of Viscofan S.A. or any of its employees or representatives. The use of the information contained herein is made at the sole discretion and risk of the reader.

America - Asia - Europe - Oceania

PRODUCT PRESENTATION

Casing can be clear or colored. Available calibers range from caliber/size 36 mm - #1ST to 180 mm - #14.

It can be delivered on reels, cut pieces or shirred strands. Cut pieces can also be supplied tied or with a clip. Casing can be prestuck (PS) in order to remove air from product surface.

Casing can be supplied ready to use in reels (Redi- Reel®) or shirred (T-Shirr®).

Casing can be printed up to six colors on each side.

Viscofan Fibrous can be produced in three varieties that will meet the specific requirements for each type of product.

- Regular for most of the applications, both cooked and dry cured.
- Zip™ variety for enhanced peeling performance (ZIP1, ZIP2 and ZIP-It).
- FRD for those applications where sufficient cling is required for processing maintaining good peelability afterwards.
- Securex® when extra meat cling is required (PSX range, SEC, SEC2, DSX, HCSX, FSX and SCSX).

Each one of those varieties can be produced in the Ergo version that improves the grip on the casing.

STORAGE RECOMMENDATIONS

Storage	<i>Avoid excessive heat (>35 °C / 95 °F) or temperatures below 39 °F (4 °C)</i>
	<i>Humidity loss should be avoided</i>
	<i>Keep boxes closed and stored at 70 % RH</i>
Processing	<i>Product must be soaked in water between 86°F and 104 °F (30-40 °C) for a minimum of 30-60 minutes (pieces) and 60 minutes (shirred material)</i>
	<i>Recommended Stuffing Diameter must be always observed (RSD included in the document)</i>
	<i>Redi-Reel® and T-Shirr® are ready to use materials so soaking is not required</i>
	<i>Recommended stuffing diameters vary slightly to the need to soak material</i>
	<i>Please refer to the specific RSD chart for Ready to Stuff materials</i>

BASIC CHEMICAL COMPOSITION

Cellulose	52 - 72 %
Glycerin	20 - 24 %
Moisture	4 - 22 %
Oil	0 - 2 %

*When adhesion or release agents/colors are used as surface treatments they are approved for food contact materials. In case of converted material oil or plasticizers may be used to facilitate the process.

Viscofan keeps the right to modify this sheet totally or partially. The information included herein has been collected by Viscofan S.A. in good faith and to the best of its knowledge. It must be considered as a communication of the experience accumulated over the years by Viscofan S.A. without any implicit or explicit guarantee from the side of Viscofan S.A. or any of its employees or representatives. The use of the information contained herein is made at the sole discretion and risk of the reader.

America - Asia - Europe - Oceania

Viscofan SA. Poligono Industrial Berroa. C/ Berroa 15-4ª Planta. 31192 Tajonar - Navarra. Spain. Tel: +34 948 198 444. Fax: +34 948 198 431.
www.viscofan.com

USE RECOMMENDATIONS

Nominal Caliber	Recommended Stuffing Diameter		Size	Aprox. stuffed weight	
	mm	inches		lbs./ft.	Kg/m
35	35	1,37	1SM	0,65	0,97
36	36	1,41	1ST	0,69	1,03
37	38	1,49	1SR, 1SRT	0,77	1,15
38	41	1,61	1SP	0,90	1,34
40	43	1,7	1SK	1,00	1,49
42	45	1,76	1SD, 1SDX	1,07	1,60
43	46	1,8	1SLS	1,12	1,67
44	46	1,81	1SL	1,14	1,69
45	49	1,93	1S	1,29	1,92
45	50	1,97	1A, 1AC	1,35	2,00
46	51,5	2,03	1MJ	1,43	2,13
47	51,8	2,04	1MJB, 1MP	1,44	2,15
47	52	2,05	1M, 1ML, 1MT, 1MV	1,46	2,17
48	53	2,09	1, 1H	1,51	2,25
50	54	2,14	1 – 1/4	1,59	2,36
53	56	2,19	1 – 1/2, 1 – 1/2H	1,66	2,48
55	58	2,28	2GN	1,80	2,68
57	59	2,32	2G	1,87	2,78
58	61	2,4	2S	2,00	2,97
59	64	2,51	2, 2P	2,19	3,25
60	66	2,59	2 – 1/4	2,33	3,46
65	70	2,77	2-1/2K, 2-1/2P	2,66	3,96
66	72	2,83	2 – 1/2	2,78	4,13
68	75	2,95	2 – 1/2N	3,02	4,49
70	79	3,1	3 – 1/2	3,33	4,96
71	80	3,15	4S	3,44	5,12
73	83	3,25	4SD	3,66	5,45
75	84	3,31	4	3,80	5,65
80	86	3,4	4L	4,01	5,97
80	87	3,43	5, 5FT	4,08	6,07
81	89	3,5	5C	4,25	6,32
83	89	3,5	5G	4,25	6,32
85	92	3,6	5GT	4,49	6,69

Nominal Caliber	Recommended Stuffing Diameter		Size	Aprox. stuffed weight	
	mm	inches		lbs./ft.	Kg/m
85	94	3,7	5N, 5NM	4,75	7,07
87	98	3,86	5 – 1/2H	5,17	7,69
88	99	3,9	6M	5,28	7,85
90	101	3,98	6G, 6GS, 6GT	5,49	8,18
93	103	4,05	6	5,69	8,47
93	104	4,09	6K, 6KS	5,80	8,63
95	105	4,13	6L, 6LS	5,92	8,80
100	107	4,24	6 – 1/2	6,24	9,28
100	109	4,3	6 – 1/2K	6,41	9,54
101	110	4,34	6-1/2L, 6-1/2N	6,53	9,72
103	113	4,43	7, 7GS	6,81	10,13
104	113	4,45	7B, 7G	6,87	10,22
105	115	4,53	7R	7,12	10,59
106	117	4,6	7-1/2, 7-1/2G	7,34	10,92
107	118	4,65	7 1/2S	7,50	11,16
108	119	4,68	7-1/2K, KS	7,60	11,30
109	120	4,72	8M, 8MS	7,73	11,50
110	122	4,81	8, 8G	8,02	11,94
115	124	4,88	8-1/2, 8-1/2G	8,26	12,29
118	128	5,06	9	8,88	13,21
119	130	5,1	9F	9,02	13,42
120	131	5,15	9N, 9G	9,20	13,69
130	137	5,38	9-1/2, 9-1/2G	10,04	14,94
135	142	5,58	10, 10D	10,80	16,07
140	147	5,77	10F	11,55	17,18
145	150	5,92	11, 11G	12,16	18,09
150	155	6,12	11D, 11F	12,99	19,33
152	157	6,17	11 – 1/2	13,20	19,65
157	167	6,56	12, 12H	14,93	22,21
160	173	6,83	12F, 12G	16,18	24,08
170	182	7,16	13, 13G	17,78	26,46
180	198	7,8	14, 14G	21,10	31,40

BEST BEFORE DATE

Recommended period of use from delivery date is 1 year for ready to use material and 2 years for other presentations.

This is not a shelf life, as the casing contains no perishable raw materials. When stored properly, fibrous casing can be safely used beyond the mentioned periods.

FOOD LEGISLATION

Viscofan Fibrous casings are not intended at being consumed together with the products they contain. In case the product is commercialized with the casing we suggest following the labelling recommendation according with Regulation (UE) 1169/2011: Remove casing before consumption.

They comply with USA Regulation Title (Chapter) 21 of CFR, Section (paragraph) 176.170. Components of paper and paperboard in contact with aqueous and fatty foods (food stuff) and European Regulation (EC) 1935/2004 on materials intended to come into contact with food.

A) ALLERGENS

No allergen substances, in accordance with European Regulation (EU) 1169/2011 are used during manufacture of Viscofan casings.

Viscofan keeps the right to modify this sheet totally or partially. The information included herein has been collected by Viscofan S.A. in good faith and to the best of its knowledge. It must be considered as a communication of the experience accumulated over the years by Viscofan S.A. without any implicit or explicit guarantee from the side of Viscofan S.A. or any of its employees or representatives. The use of the information contained herein is made at the sole discretion and risk of the reader.

America - Asia - Europe - Oceania

Viscofan SA. Poligono Industrial Berroa. C/ Berroa 15-4ª Planta. 31192 Tajonar - Navarra. Spain. Tel: +34 948 198 444. Fax: +34 948 198 431.
www.viscofan.com

B) GMO

Original raw materials and process coadjutants used in Viscofan casings do not contain genetically modified organisms, and specific labeling is not required in accordance to European Regulations (EC) 1829/2003 and 1830/2003.

Note. Viscofan Documents Sharing Policy. This document is shared for the exclusive use of the recipient person / company / institution and may not be distributed to third parties without the prior written consent of Viscofan. The recipient person / company / institution must guarantee its traceability and custody at all times. In assuming the same policy, Viscofan undertakes not to share information received from our product or service providers with third parties without express knowledge.

Note. This is an electronically processed document. Valid without signature.

Viscofan keeps the right to modify this sheet totally or partially. The information included herein has been collected by Viscofan S.A. in good faith and to the best of its knowledge. It must be considered as a communication of the experience accumulated over the years by Viscofan S.A. without any implicit or explicit guarantee from the side of Viscofan S.A. or any of its employees or representatives. The use of the information contained herein is made at the sole discretion and risk of the reader.

America - Asia - Europe - Oceania

Viscofan SA. Poligono Industrial Berroa. C/ Berroa 15-4ª Planta. 31192 Tajonar – Navarra, Spain. Tel: +34 948 198 444. Fax: +34 948 198 431.
www.viscofan.com