



Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au

Issue Date: 6th January 2020

SPECIFICATION SHEET

Code: NCPLWM23T

Description: WRAP MACHINE 500MM 1420M 23UM NAT

Physical Properties		Unit	Tolerance +/-	Specification	Test Method
Thickness		micron	1um	23	Thickness Gauge
Width		mm	5mm	500	Measuring Tape
Length		metres	5m	1420	High Speed Encoder
Density		g/cm³		0.91-0.92	ASTM D-1505
Mechanical Properties		Unit	Tolerance	Specification	Test Method
Tensile Strength	MD	MPA	10 %	23.2	ASTM D 882
	TD		10 %	18.9	
Break Elongation	MD	%	10 %	365	
	TD		10 %	585	
Dart Drop		g	10 %	61.5	ASTM D 1709
Puncture		kg	10 %	20.5	FPT-750
Stretching Level		%		350	
Grade		MS 250			
Country of Origin		Malaysia			
Material		Polyethylene Stretch Film			

Julie Butcher

Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.

