



Issue Date: 13th January 2020

Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au

SPECIFICATION SHEET

Code: REDUSBOK/4-15

Description: BOOT REDBACK TAN ELASTIC SIDED SAFETY TOE

Ankle height Elastic Sided boot (170mm from wear surface to top of boot). All leather upper with external galosh counter support. Sole / insole design incorporates impact absorbing features to reduce heel strike and a wedge profile sole giving greater surface area for stability and traction.

Workplace

Requirements: To provide comfort and protection from entry of foreign matter during extended periods of wear in heavy industrial environments. Features lightweight, insulated and shock absorbing construction for comfort on concrete floors.

General User

Properties:

To maintain the health and performance of foot and related structures.
* Enhance specific foot functions including shock-absorbency and slip resistance
* Encourage normal foot functioning including maintaining forefoot flexibility, fore-to-hind foot and heel stability



Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.





Bunzl Australasia
Limited

Head Office
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia
Tel: +61 2 9737 2100

Issue Date: 13th January 2020

New Zealand
Unit D, 373 Neilson
Street, ONEHUNGA,
AUCKLAND NZ
Tel: 0011 64 9 634 9013
www.bunzl.com.au

SPECIFICATION SHEET

Materials:

Upper:	2.4 – 2.6 mm Full Grain Cow Hide Full chrome tannage with oiled finish
Colour:	Claret
Lining:	1.1 – 1.3 mm Breathable Woven Safety Lining
Insole:	3mm Non-Woven with special bacteria resistance
Footbed:	Removable "Cambrelle" bonded padded Footbed with contoured heel cup and arch support for additional support, hygiene and volumetric control.
Heel stiffener:	Thermoplastic heavy duty
Closure:	Elastic sided (4") – 2 pull on loops.
Toecap:	Steel Toe Cap to AS/NZS 2210.2
Thread:	20 gauge minimum poly/cotton to AS/NZS 2210.
Sole:	Compression moulded TPU hard wearing outsole Direct Injection Air Cushion Hydrolysis Resistant Polyurethane Midsole 160C Heat resistance High resistance to oils/acid

Julie Butcher

Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate and will be valid until revoked.

