



food processor supplies

9th February 2017

Bunzl Food Processor
Supplies Pty Ltd
ABN 17 000 011 441

Sydney
34-48 Cosgrove Road
Enfield NSW 2136
Locked Bag 3011
Burwood NSW 2134
Australia

Tel: +61 2 9737 2100
Fax: +61 2 9642 0229
www.bunzl.com.au

SPECIFICATION SHEET

Code: TI34278

Description: PAPER OIL FILTER NON WOVEN PK 50

Fibre Blend: 70% Polyester / 30% Viscose Rayon

Blender Type: Acrylate

Weight: 52gsm

Thickness: .38mm

Tensile Strength: 7.68 / 1.62kg

Elongation: 14 / 28%

Tear Strength: 0.52 / 0.32kg

Mullens Burst Strength: Dry 130kpa – Wet 70kpa

Air Permeability: 3400 litres/m²/sec – 680 mm/sec or 68 ml/cm²

Water Permeability: 168 litres/m²/sec – (P = 50mm H₂O)


Micron Rating: 80>98 microns (Nominal) – Wet Sieve 095

Food Grade: Virgin Fibres to FDA Sect 21 (CFR 176170) and AS4020 standards

Fibre Lay: Parallel

Characteristics: A new product especially made for fry oil filtration. The media has excellent loftiness in the fibre structure while maintaining a consistent lay of fibres. It creates a base mat to commence sediment collection and the laying up process of contaminants and fines.

1035 is perfect to inbuilt fryer filter systems or wheel up filter machines.


Julie Butcher

Business Analyst/ Quality Assurance Manager

Disclaimer:

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate.

