



PRODUCT: **tesa 4262**

DESCRIPTION: General Purpose Polypropylene Carton Sealing Tape.

APPLICATIONS: High volume, packaging and carton sealing for light to medium cartons.

TECHNICAL SPECIFICATIONS:

Backing Material:	Bidirectional Polypropylene
Adhesive Type:	Synthetic Co-Polymer
Total Thickness:	0.048mm
Tensile Strength:	123 N/25mm
Adhesive Power:	8.8 N/25mm
Elongation at Break:	90 - 100%
Colours Available:	Brown, Transparent
Operating Temperature:	-50°C - + 100°C
Application Range:	+ 4°C - 40°C
Storage Range:	0°C - 50°C

PRODUCT PROPERTIES: Suitable for use on recycled board and under shrink wrap.

tesa self-adhesive tapes are used successfully in many sectors, to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problem. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We therefore recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.