



# food processor supplies

26<sup>th</sup> October 2016

## SPECIFICATION SHEET

Bunzl Food Processor  
Supplies Pty Ltd  
ABN 17 000 011 441

Sydney  
34-48 Cosgrove Road  
Enfield NSW 2136  
Locked Bag 3011  
Burwood NSW 2134  
Australia

Tel: +61 2 9737 2100  
Fax: +61 2 9642 0229  
www.bunzl.com.au

**Code:** BF516352001  
**Description:** VAC SHRINK BAG 100UM 300X350MM

PROPERTIES	UNITS	TYPICAL VALUES
<b>THICKNESS</b>	µm	100
<b>SHRINKAGE (90°C)</b>	%	M.D. 25 T.D. 30
<b>O2-TRAN 23°C, 75% R.H.</b> ASTM F 1927	cc/m <sup>2</sup> /24h/1atm	21
<b>CO2-TRAN 23°C, 0% R.H.</b> ASTM F 2476	cc/m <sup>2</sup> /24h/1atm	150
<b>WVTR 38°C, 90% R.H.</b> ASTM F 1249	gr/m <sup>2</sup> /24h	8
<b>TENSILE STRENGTH</b> ASTM D 882	N/mm <sup>2</sup>	M.D. 110 T.D. 100
<b>ELONGATION AT BREAK</b> ASTM D 882	%	M.D. 140 T.D. 150
<b>HAZE</b> ASTM D 1003	%	14
<b>GLOSS</b> ASTM D 2457	G.U.	80
<b>RECOMMENDED STORAGE CONDITIONS</b>		To be stored below 25°C and 65% RH, away from steam pipes or direct sunlight.
<b>APPLICATION</b>		High abuse shrink bag

Julie Butcher  
Business Analyst/ Quality Assurance Manager



**Disclaimer:**

The information provided is based on the product's manufacturer and a copy of manufacturer's declaration is held on file. We have every reason to believe that the information provided is accurate.