

## Specifications Cordstrap Composite Lashing Solution: CC105 UF & CB10

Performance Specifications	
Performance System (strap & buckle)	
System Breaking Strength*	2600 daN / 5845 lbf
Performance Strap	
Linear Breaking Strength*	1600 daN / 3600 lbf
Elongation	<7%
Elongation at Break	13% - 17%
Certification	German Lloyd, AAR Grade 4

Strap Specifications	
Dimensions	
Width*	32 mm / 1.1/4"
Thickness*	1,2 mm / 3/64"
Material	High tenacity polyester filament yarn and Homopolymer Polypropylene
Coil	
Length per Coil**	230 meters / 750 feet
Core Diameter	200 mm / 8"
Packaging	
Carton Box	2 coils per box
Dimensions*	390 x 390 x 354 mm / 15.3/8" x 15.3/8" x 14"
Box Weight*	19 kg / 42 lbs
Product Code	7289000
Pallet Box	
Dimensions*	30 coils per box
Box Weight*	1181 x 781 x 890 mm / 46.9" x 31.1" x 35"
Product Code	285 kg / 628 lbs
	7289900

Buckle Specifications	
Dimensions	
Width*	32 mm / 1.1/4"
Material	Galvanized steel wire
Packaging	
Carton Box**	125 pieces per box
Dimensions*	266 x 166 x 166 mm / 10.1/2" x 6.5/8" x 6.1/4"
Box Weight*	11 kg / 25 lbs
Product Code	7355500



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance

Recommended Tensioner(s)	
<b>Pneumatic Tensioner</b>	CT35 PN 300 – 1100 daN / 375 – 2475 lbf 19 mm – 32 mm / 3/4" – 1.1/4" 0,7 mm – 1,6 mm / 1/32" – 1/16" 4,2 kg / 9.3 lbs 7566100
<b>Manual Tensioner</b>	CT40 (2) 200 – 800 daN / 450 – 1800 lbf 19 mm – 40 mm / 3/4" – 1 5/8" 0,6 mm – 1,5 mm / 1/32" – 1/16" 2,5 kg / 5.5 lbs 7502400
<b>Manual Tensioner</b>	CTT40 200 – 800 daN / 450 – 1800 lbf 19 mm – 40 mm / 3/4" – 1.5/8" 0,6 mm – 1,8 mm / 1/12" – 5/64" 2,5 kg / 5.5 lbs 7502500

Accessories	
<b>Anti-Slip Mats</b>	Different types and sizes available. Your Cordstrap cargo securing specialist can advise you about the best Anti-Slip Mat for your application.
<b>Edge Protection</b>	Different types and sizes available. Your Cordstrap cargo securing specialist can advise you about the best Edge Protection for your application.
<b>Coil Dispenser with Buckle Tray</b> Product Code Portable Version Product Code Static Version	7538000 7544000

\* Tolerance of +/- 10%

\*\* Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between 5°C and 25°C / 41°F and 77°F

All information provided is based on accuracy at time of creation



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance