



MANUFACTURE SPECIFICATION

OH&S FOOT-FOOTWEAR MANAGEMENT

| | | |
|------------|---------------|---------------|
| CUSTOMER: | DATE:05/05/15 | REVIEW DATES: |
| CODE: UBOK | | |

MODEL DESCRIPTION: E/S BOBCAT SOFT TOE CLARET OIL KIP

Ankle height Elastic Sided boot (170mm from wear surface to top of boot). All leather upper with external galosh counter support. Sole / insole design incorporates impact absorbing features to reduce heel strike and a wedge profile sole giving greater surface area for stability and traction.

Sizes: 2 >15 incl half sizes 4 ½ to 11 ½

SPECIFIC WORKPLACE REQUIREMENTS:

To provide comfort and protection from entry of foreign matter during extended periods of wear in heavy Industrial environments. Features lightweight, insulated and shock absorbing construction for comfort on concrete floors. The footwear is to provide a quick release system to assist ingress and egress of foot whilst maximising ankle support.

GENERAL USER PROPERTIES:

to maintain the health and performance of foot and related structures ~

- ① Enhance specific foot functions including shock-absorbency and slip resistance
- ② Encourage normal foot functioning including maintaining forefoot flexibility, fore-to-hind foot and heel stability

MATERIALS:

| | |
|-----------------|---|
| Upper: | 2.4- 2.6mm Full Grain Premium cow hide |
| Colour: | Claret Oiled finish |
| Insole: | 3mm Non-Woven with special bacteria resistance |
| Footbed: | Removable "Cambrelle" bonded padded Footbed with contoured heel cup and arch support for additional support, hygiene and volumetric control. |
| Heel stiffener: | Thermoplastic heavy duty |
| Closure: | Elastic sided (4") – 2 pull on loops. |
| Toecap: | Thermoplastic Heavy Duty |
| Thread: | 20 gauge minimum poly/cotton to AS/NZS 2210. |
| Sole: | Compression moulded TPU hard wearing outsole Direct Injection Air Cushion Hydrolysis Resistant Polyurethane Midsole 160C Heat resistance High resistance to oils/acids |