



3M™ Half Face Respirator 7500 Series

3M's Half Face Reusable Respirators 7500 Series have set a high standard in comfort. The 3M™ Cool Flow™ Exhalation valve reduces breathing resistance, helping to minimise heat build-up in the respirator, increasing your comfort.

Available in three sizes, all respirators have the 3M™ Bayonet Connection System which fits 3M's range of twin, lightweight,

cartridges and filters. These provide protection against gases, vapours and particulates (depending on your needs). The twin filter design has a low profile and is well balanced. These half face respirators can also be used with 3M™ Supplied-Air Systems.

Meets the performance requirements of AS/NZS 1716:2012.

Features and Benefits:

Comfort

- + Soft silicon face seal for extra comfort and durability
- + Proprietary 3M™ Cool Flow™ Exhalation valve provides low breathing resistance and minimises heat build-up in the respirator
- + Ideal for working in hot and humid conditions or during prolonged use
- + Thin nose bridge area for reduced pressure and improved comfort



Convenience





- + Drop down harness feature for added convenience during breaks
- + Fits well with 3M Head and Eye Protection
- + Respirator design helps reduce fogging when wearing eye protection
- + Unique valve design reduces dust and dirt build-up improving hygiene and reliability

Flexibility

- + Optional supplied air connection (SA-2000 or SA-2100)

Spare parts

A range of spare parts or components are available. Below are the most common spare parts.

Product Code	Description
 7582	Inhalation Valve - Blue
 7583	Exhalation Valve - Blue
 7580	Replacement Harness Straps
 7581	Head Harness Assembly



3M™ Half Face Respirator 7500 Series

3M 7501 – small (light blue)

3M 7502 – medium (blue)

3M 7503 – large (dark blue)

3M™ Respirator Cleaning Wipe 504



The 504 Cleaning Wipes are alcohol-free pre-moistened towelettes for cleaning all reusable respirators without damaging them.